

## Technical Data – HB710

Aluminium foil coated with conductive Acrylic adhesive.


### Product description

- Conductive Single Coated Acrylic Adhesive Tape

### Construction

- Aluminium Foil (40 µm)
- Conductive Acrylic Adhesive
- Release Liner

### Technical data



Item	Unit		Spec.	
Total thickness	µm	Inch	85±5	.003
Peel Strength	g/in	lb/inch	750	1.7
Heat Temperature	°C	°F	130	266
Electrical Resistance	Ω.cm	Ω.inch	10 <sup>-1</sup> ~ 10 <sup>-3</sup>	.25 ~ .003

### Application

1. Shielding of signal cable
2. Repair for shielding signal cable or FCC
3. Blinding the end of knitted wire mesh of shielding cable
4. For shield leaking or invading electromagnetic waves
5. Tape for EMR / RFI shielding

### Note

Unless stated otherwise all values given are average. All of the tapes in our range should be thoroughly tested on the substrates in the particular application they are intended for. Hi-Bond Tapes Ltd. will not be responsible for product failure unless full testing has been completed. The customer has to decide on the tapes suitability for the intended application.



### High Performance Tapes and Adhesive Products

1 Crucible Road, Phoenix Parkway, Corby, Northamptonshire NN17 5TS  
 Telephone: +44 (0)1536 260022 Fax: +44 (0)1536 260044  
 Email: sales@hi-bondtapes.co.uk  
 www.hi-bondtapes.com

Company Registration No. 3985595

