



## Technical Data – VST4110G

Excellent for bonding a wide range of metals including stainless steel and aluminium. Very good with powder coated painted surfaces and automotive paints.


### Product description

- Foamed Acrylic Tape
- Colour: Grey
- Soft, tacky and conformable
- Ideal for use in engineering, window and door and sign and display manufacturing

### Construction

- Red PE Liner
- Acrylic adhesive
- Available in log rolls or cut to specific widths

### Technical data



Item	Unit		Spec.		Test method
<b>Total thickness</b>	mm	in	1.1(±0.1)	0.043(±0.004)	-
<b>Density</b>	kg/m <sup>3</sup>	Lb/ft <sup>3</sup>	850	53	-
<b>180° Peel Strength</b>	g/25mm	lb/in	3900	8.7	ASTM-D-3330 (Stainless steel, room temp)
<b>Tensile Strength</b> (T-Block Test)	g/cm <sup>2</sup>	lb/in <sup>2</sup>	6000	85	ASTM-D-897 (Aluminium, room temp)
<b>Dynamic Shear</b> (after 20min)	g/cm <sup>2</sup>	lb/in <sup>2</sup>	4000	57	ASTM D-1002 (Stainless steel, room temp)
<b>Dynamic Shear</b> (after 24hrs)	g/cm <sup>2</sup>	lb/in <sup>2</sup>	6300	90	ASTM D-1002 (Stainless steel, room temp)
<b>Temperature Resistance</b> (Short Term)	°C	°F	160	320	-
<b>Temperature Resistance</b> (Long Term)	°C	°F	100	212	-
<b>Low Temp. Resistance</b>	°C	°F	-40	-40	-
<b>UV Resistance</b>	-	-	Good	-	-

**Applications:** Engineering, Sign and display, Plastics and a wide range of metals

**Note:** Unless stated otherwise all values given are average. All of the tapes in our range should be thoroughly tested on the substrates in the particular application they are intended for. Hi-Bond Tapes Ltd. will not be responsible for product failure unless full testing has been completed. The customer has to decide on the tapes suitability for the intended application.

### High Performance Tapes and Adhesive Products

1 Crucible Road, Phoenix Parkway, Corby, Northamptonshire NN17 5TS  
 Telephone: +44 (0)1536 260022 Fax: +44 (0)1536 260044  
 Email: sales@hi-bondtapes.co.uk  
 www.hi-bondtapes.com

Company Registration No. 3985595

