


Technical Data – HB254

Product description

- Polyester Film Singlecoated acrylic adhesive tape
- Good adhesion and Anti-static ability

Construction

- Release Coating Layer
- Pet Film
- Anti-static Adhesive



Technical data

Item		Unit	Spec.	Test Method
Thickness	Backing	µm	25	ASTM D 3652
	Total		45±2	
Peel Adhesion		g/25mm	1000±100	ASTM D 3330 SUS 304
Tensile Strength		Kg/cm	Above 5	ASTM D 3759
Elongation		%	Above 50	
Holding Power		mm/h	1↓	SUS 304 1Kg
Surface Resistance		Ω	10-9	Hioki 3540

Unless stated otherwise all values given are average. All of the tapes in our range should be thoroughly tested on the substrates in the particular application they are intended for. Hi-Bond Tapes Ltd. will not be responsible for product failure unless full testing has been completed. The customer has to decide on the tapes suitability for the intended application.



High Performance Tapes and Adhesive Products

1 Crucible Road, Phoenix Parkway, Corby, Northamptonshire NN17 5TS
 Telephone: +44 (0)1536 260022 Fax: +44 (0)1536 260044
 Email: sales@hi-bondtapes.co.uk
 www.hi-bondtapes.com

Company Registration No. 3985595

Member of



German-British Chamber of Industry & Commerce
 Deutsch-Britische Industrie- und Handelskammer