

V1.0 23.09.19

Technical Data - HB5369

HB-5369 is a electrolyte sealing tape based on polyimide film with acrylic adhesive.

Product description

- **Excellent Chemical resistance**
- Good peel strength
- Halogen free type pigment.
- Construction
- Polyimide (25µm)
- Acrylic Adhesive (5µm)



Technical data

Item	Unit	Value	Test Method
Base Film Thickness	μm	25	ASTM D3652
Total Thickness	μm	30	ASTM D3652
Peel Strength	gf/in	500	ASTM D 3330
Elongation	%	Above 50	ASTM D 3759
Tensile Strength	Kgf/cm²	Above 1200	ASTM D3759
Appearance	-	Amber	Visual Test

Note

Unless stated otherwise all values given are average. All of the tapes in our range should be thoroughly tested on the substrates in the particular application they are intended for. Hi-Bond Tapes Ltd. will not be responsible for product failure unless full testing has been completed. The customer has to decide on the tapes suitability for the intended application.



1 Crucible Road, Phoenix Parkway, Corby, Northamptonshire NN17 5TS Telephone: +44 (0)1536 260022 Fax: +44 (0)1536 260044 email: sales@hi-bondtapes.co.uk MEMBER GERMAN-BRITISH CHAMBER OF INDUSTRY & COMMERCE www.hi-bondtapes.com